


MilkFlex[®] Suction/Discharge Hose

APPLICATIONS: DAIRY, FOOD, BEVERAGE



FEATURES/BENEFITS

- Lightweight and flexible
- Remains supple even in extremely cold temperatures
- Resists pinhole leaks during high temperature cleaning
- Reduces cracked helix problems caused by pressure surges or aging

COLOR

- White

CONSTRUCTION

- Inner tube: white FDA butyl
- Cover: white natural rubber reinforced with two fabric plies with double helix wire

FITTINGS

- ReSeal[®] reusable

TEMPERATURE RATING

- -40° to 190°F continuous

APPROVALS

- FDA, USDA, 3A, CFIA

HOSE SPECIFICATIONS

Part Number	Inside Diameter (mm)	Outside Diameter (mm)	Max. Working Pressure (PSI @ 68°)	Min. Bend Radius (in.)	Vacuum in HG	Weight (lb./ft.)
MHH-51	51	65	90	5.0	29	1.35
MHH-63	63	76	90	7.0	29	1.68
MHH-76	76	89	90	14	29	2

NOTE: All MilkFlex[®] product pressure ratings are shown at ambient temperature (68°F). As temperatures increase, working pressure and vacuum ratings will decrease. Contact factory for recommendations for assembly applications that exceed 190°F.