

Extras

Washdown Hose



FEATURES/BENEFITS

- Designed for food and beverage clean-up service
- Handles hot water up to 200°F
- Abrasion resistant, non-marking cover
- Spiral construction for excellent flexibility

COLOR

- White

CONSTRUCTION

- Inner tube/black nitrile
- Cover/white nitrile-PVC blend reinforced with two synthetic textile spiral cords

FITTINGS

- Shank style with strap or worm gear type clamp (not supplied by Saint-Gobain)

TEMPERATURE RATING


- -20° to +200°F

HOSE SPECIFICATIONS

Part Number	Inside Diameter (in.)	Outside Diameter (in.)	Working Pressure (PSI)	Weight (lb./ft.)
WDH075	3/4	1-6/32	300	0.4

NOTE: Product pressure ratings are shown at ambient temperature. As temperatures increase, working pressure and vacuum ratings will decrease. Contact factory for recommendations for assembly applications that exceed 140°F. Available only in 500-foot coil.

Steam Hose



FEATURES/BENEFITS

- Recommended for cleaning pumps, valves, tubing
- Rugged construction for harsh conditions
- Will not harden or crack during normal service life
- Vented cover resists blistering

COLOR

- Red with yellow stripe

CONSTRUCTION

- Inner tube/black EPDM
- Cover/EPDM reinforced with steel wire

FITTINGS

- Interlocking clamp style (not supplied by Saint-Gobain)

TEMPERATURE RATING

- -20° to +400°F

HOSE SPECIFICATIONS

Part Number	Inside Diameter (in.)	Outside Diameter (in.)	Working Pressure (PSI)	Weight (lb./ft.)
PCR075	3/4	1-8/32	250	0.5

NOTE: Product pressure ratings are shown at ambient temperature. As temperatures increase, working pressure and vacuum ratings will decrease. Contact factory for recommendations for assembly applications that exceed 140°F. Available only in 50-, 100- and 200-foot lengths.

SaniGard® Hose Supports



FEATURES/BENEFITS

- Designed to elevate hose to reduce cover wear, increase service life
- Exclusive saddle support eliminates hose kinking problems
- Two-part design installs easily, stays in place, and slides across pavement for handling ease

HOSE SPECIFICATIONS

Part Number	Suggested Intervals	Fits SaniGard® Hose ID Size	Weight (lb.)
HD150	10" to 16"	1-1/2"	4
HD200	12" to 18"	2"	4.8
HD250	20" to 28"	2-1/2"	5
HD300	20" to 28"	3"	5
HD400	24" to 36"	4"	5.5

NOTE: Product pressure ratings are shown at ambient temperature. As temperatures increase, working pressure and vacuum ratings will decrease. Contact factory for recommendations for assembly applications that exceed 140°F.